

Door Closer, V-Arm, TS1000

Features and Benefits



TS 1000 Overhead rack and pinion door closer with adjustable closing speed and adjustable latching action.

Variable closing force in two sizes achieved by simply turning the link, arm's power shoe: 'Weak' for leaf widths up to 850mm (closing force size 2 to EN 1154), 'Strong' for leaf widths up to 950 mm

Increased closing force due to off set installation for leaf widths up to 1100 mm (closing force size 4 to EN 1154)

Closing speed and latching action adjustable

Option: with hold-open link arm allowing the closer to hold doors open between 700 and 1500

Door closer	TS 1000 C	TS 1500	TS 2000 V	TS 2000 NV	TS 4000	TS 4000 E / R	TS 4000 EFS / RFS
Closing force	3	3/4	2 / 4 / 5	2-4	1-6 / 5-7	1-6 / 5-7	1-6
Approval for fire and smoke protection doors	■	□	□	■	■	■	■
max. door leaf width [mm]	950	≤ 950 / 1.100*	≤ 1.250	≤ 1.100	≤1.400/ ≤1.600	≤1.400/ ≤1.600	≤1.400
Link arm / Guide rail	■ / □	■ / □	■ / □	■ / □	■ / □	■ / □	■ / □
Functions / Settings							
Closing force can be continuously adjusted	□	□	□	■	■	■	■
Back check	□	□	TS 2000 V BC	TS 2000 NV BC	■	■	□
Latching action	■	■	■	■	■	■	■
Adjustable closing speed	■	■	■	■	■	■	■
Optical large display	□	□	□	□	■	■	■
Hold open position can be overridden	●, mechan.	●, mechan.	●, mechan.	●, mechan.	●, mech./ □	■, e-hydraul.	□
Integrated smoke switch	□	□	□	□	□	□/■	□/■
Freeswing function	□	□	□	□	□	□	■

■ yes □ no ● optional

Window & Door Accessories Ltd.

Richmond House, Newtown Avenue, Malahide Road Industrial Park, Dublin 17

Tel: 01-8670011 Fax: 01-8670011 Email: info@wdacc.ie Web: www.wdacc.ie

