

# Door Closer, V-Arm, TS1500

## Features and Benefits



With the TS 1500 overhead door closer, the closing speed and the end stop can be adjusted, the closing force is variable. It is optionally available with a mounting plate and is suitable for both right and left swing doors without conversion.

Door closer TS 1500 with link arm for doors with up to 1100 mm leaf widths

Closing force variable EN 3/4 for doors up to 950 or 1100 mm leaf width by simply turning the bearing block

Hydraulic end stop and closing speed can be adjusted

Can be used for right and left swing doors without conversion

Optional: Hold-open arm with a hold-open range of 70°-150°

Door closer	TS 1000 C	TS 1500	TS 2000 V	TS 2000 NV	TS 4000	TS 4000 E / R	TS 4000 EFS / RFS
Closing force	3	3/4	2 / 4 / 5	2-4	1-6 / 5-7	1-6 / 5-7	1-6
Approval for fire and smoke protection doors	■	□	□	■	■	■	■
max. door leaf width [mm]	950	≤ 950 / 1.100*	≤ 1.250	≤ 1.100	≤1.400/ ≤1.600	≤1.400/ ≤1.600	≤1.400
Link arm / Guide rail	■ / □	■ / □	■ / □	■ / □	■ / □	■ / □	■ / □
<b>Functions / Settings</b>							
Closing force can be continuously adjusted	□	□	□	■	■	■	■
Back check	□	□	TS 2000 V BC	TS 2000 NV BC	■	■	□
Latching action	■	■	■	■	■	■	■
Adjustable closing speed	■	■	■	■	■	■	■
Optical large display	□	□	□	□	■	■	■
Hold open position can be overridden	●, mechan.	●, mechan.	●, mechan.	●, mechan.	●, mechan./ □	■, e-hydraul.	□
Integrated smoke switch	□	□	□	□	□	□/■	□/■
Freeswing function	□	□	□	□	□	□	■

■ yes □ no ● optional

## Window & Door Accessories Ltd.

Richmond House, Newtown Avenue, Malahide Road Industrial Park, Dublin 17

Tel: 01-8670011 Fax: 01-8670011 Email: info@wdacc.ie Web: www.wdacc.ie

