

Door Closer, V-Arm, TS2000

Features and Benefits



TS 2000 V – Pinion door closer with variable closing force up to 1250 mm

With the TS 2000 V overhead door closer with variable closing force in accordance with DIN EN 1154 in sizes 2, 4 and 5, the closing speed can conveniently be set from the front. The stopper setting is made using the arm.

Door closer TS 2000 V with link arm for doors with up to 1250 mm leaf widths

Closing force variable EN 2/4/5 by using offset mounting

End stop adjusted using the arm, closing speed can also be adjusted

Can be used for right and left swing doors without conversion

Optional: Hold-open range 70°-150° (via the hold-open arm)

Optional: Hydraulic end stop set from the front and fixed set opening buffer (GEZE TS 2000 V BC)

Door closer	TS 1000 C	TS 1500	TS 2000 V	TS 2000 NV	TS 4000	TS 4000 E / R	TS 4000 EFS / RFS
Closing force	3	3/4	2 / 4 / 5	2-4	1-6 / 5-7	1-6 / 5-7	1-6
Approval for fire and smoke protection doors	■	□	□	■	■	■	■
max. door leaf width [mm]	950	≤ 950 / 1.100*	≤ 1.250	≤ 1.100	≤1.400/ ≤1.600	≤1.400/ ≤1.600	≤1.400
Link arm / Guide rail	■ / □	■ / □	■ / □	■ / □	■ / □	■ / □	■ / □
Functions / Settings							
Closing force can be continuously adjusted	□	□	□	■	■	■	■
Back check	□	□	TS 2000 V BC	TS 2000 NV BC	■	■	□
Latching action	■	■	■	■	■	■	■
Adjustable closing speed	■	■	■	■	■	■	■
Optical large display	□	□	□	□	■	■	■
Hold open position can be overridden	●, mechan.	●, mechan.	●, mechan.	●, mechan.	●, mech./ □	■, e-hydraul.	□
Integrated smoke switch	□	□	□	□	□	□/■	□/■
Freeswing function	□	□	□	□	□	□	■

■ yes □ no ● optional

Window & Door Accessories Ltd.

Richmond House, Newtown Avenue, Malahide Road Industrial Park, Dublin 17

Tel: 01-8670011 Fax: 01-8670011 Email: info@wdacc.ie Web: www.wdacc.ie

